



Air Cleaning Specialists, Inc.

ACSF-220-FL



CONSTRUCTION:

ELECTROPLATED GALVANIZED CLOSED END CAP WITH BOLT HOLE
ELECTROPLATED GALVANIZED OPEN END CAP
G-90 GALVANIZED EXPANDED METAL OUTER BODY
G-90 GALVANIZED EXPANDED METAL INNER CORE
230 SQUARE FEET 80/20 CELLULOSE SYNTHETIC BLENDED MEDIA
EPDM RUBBER SEALING GASKET APPLIED TO ONE OPEN END CAP
PVC SEALANT APPLIED TO BOTH ENDS
HOT MELT ADHESIVE BEAD APPLIED OUTSIDE ONLY
PACKAGED ONE PER CARTON
WEIGHT: 16 POUNDS

EFFICIENCY: (PER ASHRAE 52.2-2007)

TEST FLOW RATE: 650 CFM
INITIAL RESISTANCE: 0.25 INCHES W.G.
FINAL RESISTANCE: 4.00 INCHES W.G.
E1 (%) COMPOSITE MINIMUM AVERAGE EFFICIENCY 0.30 - 1.00 MICRON: 20%>E1
E2 (%) COMPOSITE MINIMUM AVERAGE EFFICIENCY 1.0 - 3.0 MICRON: 65%<E2
E3 (%) COMPOSITE MINIMUM AVERAGE EFFICIENCY 3.0 - 10.0 MICRON: 85%<E3
MINIMUM EFFICIENCY REPORTING VALUE: MERV 11 @ 650 CFM