



TECHNICAL DATA

FILTER CARTRIDGE SPECIFICATIONS

ITEM NUMBER: 1275141

Dimensions:	Height:	36"
	Outside Diameter:	12.75"
	Inside Diameter:	8.375"
Top End Cap:	Material:	Electro Galvanized (19 ga)
	Style:	Open with 14.25" x 16" Farr mounting flange
Bottom End cap:	Material:	Electro Galvanized (22 ga)
	Style:	Closed
Gasket:	1/2" x 5/8" x 11.25" ID isoprene sponge applied on top cap	
Inner Retainer:	Electro galvanized expanded metal 3/8" x 5/8" (9.53 mm x 15.88 mm) 72% open area	
Outer Retainer:	Electro galvanized expanded metal 3/8" x 5/8" (9.53 mm x 15.88 mm) 72% open area	
Filter Media Area:	314 ft²	
Pleat Count:	325	
Media Type:	Cellulose/Polyester Blend – Fire Retardant	
Permeability:	15 cfm/ft² @ 0.5" w.g. 112 L/sec/m² @ ΔP 20	
Maximum Temperature:	180° F	

PARTICLE EFFICIENCY BY WEIGHT. TEST DUST: AC FINE

PARTICLE SIZE:	0.5 micron-----	99.8%
	1.0 micron-----	99.9%
	2.0 micron-----	100 %