



# ProPulse™

Pleated Bag Technology

## TECHNICAL DATA

### FILTER CARTRIDGE SPECIFICATIONS

ITEM NUMBER: 1331515

<b>Dimensions:</b>	<b>Height:</b>	<b>61.13"</b>
	<b>Outside Diameter:</b>	<b>5.75"</b>
	<b>Inside Diameter:</b>	<b>4.88"</b>
<b>Configuration:</b>	<b>Bottom Load Flex Kleen – Fits 5.125" Cup</b>	
<b>Top End Cap:</b>	<b>Material:</b>	<b>Urethane</b>
	<b>Style:</b>	<b>Open</b>
<b>Bottom End cap:</b>	<b>Material:</b>	<b>Urethane</b>
	<b>Style:</b>	<b>Closed</b>
<b>Inner Retainer:</b>	<b>Electro galvanized expanded metal 3/8" x 5/8" (9.53 mm x 15.88 mm) 72% open area</b>	
<b>Outer Retainer:</b>	<b>2 Woven Bands</b>	
<b>Filter Media Area:</b>	<b>35 ft<sup>2</sup></b>	
<b>Pleat Count:</b>	<b>52</b>	
<b>Media Type:</b>	<b>100% Spun-bond Polyester</b>	
<b>Permeability:</b>	<b>20 cfm/ft<sup>2</sup> @ 0.5" w.g.</b>	
<b>Maximum Temperature:</b>	<b>180° F</b>	

### PARTICLE EFFICIENCY BY WEIGHT. TEST DUST: AC FINE

<b>PARTICLE SIZE:</b>	<b>0.5 micron-----</b>	<b>99.7%</b>
	<b>1.0 micron-----</b>	<b>99.8%</b>
	<b>2.0 micron-----</b>	<b>100 %</b>