



ProPulse™

Pleated Bag Technology

TECHNICAL DATA

FILTER CARTRIDGE SPECIFICATIONS

ITEM NUMBER: 1331522

| | |
|-----------------------------|--|
| Dimensions: | Height: 41.00" Outside Diameter: 4.63" Inside Diameter: 2.75" Flange: 6.39" |
| Configuration: | Top Load – Fits 5.25" Tube Sheet |
| Top End Cap: | Material: Urethane Style: Open |
| Bottom End cap: | Material: Urethane Style: Closed |
| Inner Retainer: | Electro galvanized expanded metal 3/8" x 5/8" (9.53 mm x 15.88 mm) 72% open area |
| Outer Retainer: | 3 Woven Bands |
| Filter Media Area: | 16 ft ² |
| Pleat Count: | 35 |
| Media Type: | 100% Spun-bond Polyester |
| Permeability: | 20 cfm/ft ² @ 0.5" w.g. |
| Maximum Temperature: | 180° F |

PARTICLE EFFICIENCY BY WEIGHT. TEST DUST: AC FINE

| | |
|---------------------------------------|-------|
| PARTICLE SIZE: 0.5 micron----- | 99.7% |
| 1.0 micron----- | 99.8% |
| 2.0 micron----- | 100 % |