



TECHNICAL DATA

FILTER CARTRIDGE SPECIFICATIONS

ITEM NUMBER: 1565932

| | | |
|-----------------------------|---|-----------------------------------|
| Dimensions: | Height: | 36" |
| | Outside Diameter: | 12.75" |
| | Inside Diameter: | 8.375" |
| Top End Cap: | Material: | Electro Galvanized (18 ga) |
| | Style: | Open with 3/4" lip flange |
| Bottom End cap: | Material: | Electro Galvanized (22 ga) |
| | Style: | Closed |
| Gasket: | 1/2" x 1/2" x 13" ID Neoprene applied on top cap under lip flange toward filter body | |
| Inner Retainer: | Electro galvanized expanded metal 3/8" x 5/8" 72% open area | |
| Outer Retainer: | Electro galvanized expanded metal 3/8" x 5/8" 72% open area | |
| Filter Media Area: | 277 ft² | |
| Pleat Count: | 280 | |
| Media Type: | Cellulose/Polyester Blend (80/20) | |
| Permeability: | 15 cfm/ft² @ 0.5" w.g. | |
| Maximum Temperature: | 180° F | |

PARTICLE EFFICIENCY BY WEIGHT. TEST DUST: AC FINE

| | | |
|-----------------------|------------------------|--------------|
| PARTICLE SIZE: | 0.5 micron----- | 99.8% |
| | 1.0 micron----- | 99.9% |
| | 2.0 micron----- | 100 % |