



TECHNICAL DATA

FILTER CARTRIDGE SPECIFICATIONS

ITEM NUMBER: 1567343

Dimensions:	Height:	20"
	Outside Diameter:	13.82" and 16.67"
	Inside Diameter:	10.60"
Top End Cap:	Material:	Electro Galvanized (22 ga)
	Style:	Open with lip flange
Bottom End cap:	Material:	Electro Galvanized (22 ga)
	Style:	Closed
Gasket:	5/8" x 5/8" x 14.00" ID isoprene sponge applied on flange of top cap	
Inner Retainer:	Electro galvanized expanded metal 3/8" x 5/8" (9.53 mm x 15.88 mm) 72% open area	
Outer Retainer:	Electro galvanized expanded metal 3/8" x 5/8" (9.53 mm x 15.88 mm) 72% open area with polywrap	
Filter Media Area:	136 ft ²	
Pleat Count:	327 +/- 2	
Media Type:	Cellulose/Polyester Blend - Fire Retardant	
Permeability:	14 cfm/ft ² @ 0.5" w.g. 112 L/sec/m ² @ ΔP 20	
Maximum Temperature:	180° F (82.22° C)	

PARTICLE EFFICIENCY BY WEIGHT. TEST DUST: AC FINE

PARTICLE SIZE:	0.5 micron-----	99.8%
	1.0 micron-----	99.9%
	2.0 micron-----	100 %