



## TECHNICAL DATA

### FILTER CARTRIDGE SPECIFICATIONS

ITEM NUMBER: 1568263

<b>Dimensions:</b>	<b>Height:</b>	35.5"
	<b>Outside Diameter:</b>	14.96 & 12.75"
	<b>Inside Diameter:</b>	8.5"
<b>Top End Cap:</b>	<b>Material:</b>	Electro Galvanized (22 ga)
	<b>Style:</b>	Open
<b>Bottom End cap:</b>	<b>Material:</b>	Electro Galvanized (22 ga)
	<b>Style:</b>	Closed
	<b>Bolt Hole:</b>	0.54"
<b>Gasket:</b>	1/2" x 1/2" x 9.59" ID isoprene sponge applied on open cap	
<b>Inner Retainer:</b>	Electro galvanized expanded metal 3/8" x 5/8" (9.53 mm x 15.88 mm) 72% open area	
<b>Outer Retainer:</b>	2 Woven Bands	
<b>Filter Media Area:</b>	99 ft <sup>2</sup>	
<b>Pleat Count:</b>	132	
<b>Media Type:</b>	Cellulose/Polyester Blend	
<b>Permeability:</b>	14 cfm/ft <sup>2</sup> @ 0.5" w.g. 112 L/sec/m <sup>2</sup> @ ΔP 20 mm w.g.	
<b>Maximum Temperature:</b>	180° F	

### PARTICLE EFFICIENCY BY WEIGHT. TEST DUST: AC FINE

<b>PARTICLE SIZE:</b>	0.5 micron-----	99.8%
	1.0 micron-----	99.9%
	2.0 micron-----	100 %