

ProTura®

Nanofiber Technology

TECHNICAL DATA

FILTER CARTRIDGE SPECIFICATIONS

ITEM NUMBER: NF20171

Dimensions:	Height:	26"
	Outside Diameter:	12.75"
	Inside Diameter:	8.375"
Top End Cap:	Material:	Electro Galvanized (22 ga)
	Style:	Open
Bottom End cap:	Material:	Electro Galvanized (22 ga)
	Style:	Closed
	Bolt Hole:	0.54"
Gasket:	1/2" x 1/2" x 10.25" ID isoprene applied on Top cap	
Inner Retainer:	Electro galvanized expanded metal 3/8" x 5/8" (9.53 mm x 15.88 mm) 72% open area	
Outer Retainer:	2 Nylon bands with hot melt overlay	
Filter Media Area:	159 ft ²	
Pleat Count:	227 +/- 2	
Media Type:	ProTura Nanofiber Technology	
Permeability:	20 cfm/ft ² @ 0.5" w.g. 160 L/sec/m ² @ ΔP 20 mm w.g.	
Maximum Temperature:	180° F (82.22° C)	
Minimum Efficiency Reporting Value:	Merv 15 @ 500 cfm	
Particle Efficiency:	99.99% @ 0.5 micron	