

ProTura®

Nanofiber Technology

TECHNICAL DATA

FILTER CARTRIDGE SPECIFICATIONS

ITEM NUMBER: NF20310

Dimensions:	Height:	26"
	Outside Diameter:	12.75"
	Inside Diameter:	8.375"
Top End Cap:	Material:	Type 304 Stainless Steel
	Style:	Open
Bottom End cap:	Material:	Type 304 Stainless Steel
	Style:	Closed
	Bolt Hole:	1.187"
Gasket:	1/2" x 1/2" x 10.25" ID isoprene applied on Top cap	
Inner Retainer:	304 Stainless Steel expanded metal 3/8" x 5/8" (9.53 mm x 15.88 mm) 72% open area	
Outer Retainer:	304 Stainless Steel expanded metal 3/8" x 5/8" (9.53 mm x 15.88 mm) 72% open area	
Filter Media Area:	226 ft ²	
Pleat Count:	325 +/- 2	
Media Type:	Premium Proprietary Cellulose/ Polyester Blend With ProTura Nanofiber Technology	
Permeability:	25 cfm/ft ² @ 0.5" w.g. 186.4 L/sec/m ² @ ΔP 20 mm w.g.	
Maximum Temperature:	180° F (82.22° C)	
Minimum Efficiency Reporting Value:	Merv 15 @ 900 cfm	
Particle Efficiency:	99.99% @ 0.5 micron	