



TECHNICAL DATA

FILTER CARTRIDGE SPECIFICATIONS

ITEM NUMBER: 1375319 GT

Dimensions:	Height:	26"
	Outside Diameter:	12.75" & 17.50"
	Inside Diameter:	8.375"
Top End Cap:	Material:	Electro Galvanized (22 ga)
	Style:	Open Conical
Bottom End cap:	Material:	Electro Galvanized (22 ga)
	Style:	Open
	Bolt Hole:	
Gasket:	1/2" x 1/2" x 15.50" ID	
Inner Retainer:	Electro galvanized expanded metal 3/8" x 5/8" (9.53 mm x 15.88 mm) 72% open area	
Outer Retainer:	Electro galvanized expanded metal 3/8" x 5/8" (9.53 mm x 15.88 mm) 72% open area	
Filter Media Area:	248ft²	
Pleat Count:	355	
Media Type:	Premium Proprietary Polyester / Glass Blend	
Permeability:	20 cfm/ft² @ 0.5" w.g. 160 L/sec/m² @ ΔP 20	
Maximum Temperature:	180° F (82.22° C)	



TECHNICAL DATA

FILTER CARTRIDGE SPECIFICATIONS

ITEM NUMBER: 1375319 GT

ASHRAE STANDARD 52.1 – 1992

Test Flow Rate	500 CFM
Initial Resistance	0.36" WG
Initial Atmospheric Dust Spot Efficiency	62.2%
Average Atmospheric Dust Spot Efficiency	90%
Average AC Fine Dust Weight Arrestance	100%
SAE Fine Dust Holding Capacity	4250 g

Initial Dust Spot	62.2%
Dust Spot @ 1" WG	87.0%
Dust Spot @ 2" WG	95.5%
Dust Spot @ 3" WG	99.0%

PARTICLE EFFICIENCY BY WEIGHT. TEST DUST: AC FINE

PARTICLE SIZE:	0.5 micron-----	99.9%
	1.0 micron-----	99.9%
	2.0 micron-----	100 %